

# Cronus

Sub info here

A moderate linear light ideal for suspending or surface mounting with in office, school, museum or hotel application. Available with dimming, DALI connection and custom finishes. Comes standard with Opal PMMA Diffuser, with low glare options available. Also available in Surface, Wall and Track mount, with both direct, indirect and direct/indirect illumination options.

<b>POWER (W)</b>	15W / 30W PER METER (CUSTOM AVAILABLE)
<b>COLOUR TEMPERATURE (K)</b>	2700K / 3000K / 4000K / 6000K / RGB
<b>DELIVERED LUMEN OUTPUT</b>	1270lm/m (15W), 2521lm/m (30W/m)
<b>CRI</b>	>90
<b>BEAM ANGLE (B)</b>	W43 x H64 x Custom Lengths
<b>ROTATE ANGLE</b>	N/A
<b>IP RATING</b>	IP20
<b>FINISH (F)</b>	WHITE /BLACK/ CUSTOM RAL
<b>INSTALLATION</b>	SURFACE / WALL MOUNT / PENDANT / TRACK
<b>DIMMING OPTIONS</b>	DALI OPTION AVAILABLE
<b>DRIVER</b>	240V INTEGRAL
<b>STANDARD LENGTH</b>	CUSTOM

**ORDER CODE:** EXCRO-W-K-B-F

